

GAMMEX® Non-Latex PI

S U R G I C A L G L O V E S

Polyisoprene, skin-friendly surgical glove with a soft glove formulation delivering extra comfort

KEY FEATURES AND BENEFITS:

- Softer and 'stretchier' PI glove featuring superior comfort compared to Ansell's latex gloves
- Smooth with micro-textured finish for exceptional instrument handling and grip
- Free from chemical accelerators known to cause chemical Type IV allergies and sensitivities for optimized allergenic profile
- The DERMASHIELD™ Technology internal coating facilitates dry and damp donning as well as intra-operative changes

Recommended For

- All surgeries, especially high risk procedures in orthopaedics, trauma, and cardiac
- Extra comfort during long, sustained procedures
- Protection from chemical accelerators such as thiurams, carbamates and mercaptos known to cause chemical Type IV allergies
- Having passed the Mouse Embryo Assay (MEA) test, may be used for In Vitro Fertilization (IVF) procedures

FEATURED TECHNOLOGIES



GAMMEX® Innovation that Protects

Driven by innovation, GAMMEX® surgical gloves are engineered to respond to the evolving user needs of the surgical community. Featuring unique formulations and cutting-edge technologies, ergonomic comfort and superior protection, healthcare workers around the world entrust their hands to ours.

GAMMEX® Non-Latex PI

S U R G I C A L G L O V E S

PRODUCT INFORMATION

Material	PI (Polyisoprene)
Powder Content	Powder-Free
Color	White
Thickness	Standard
Cuff Style	Beaded with SUREFIT™ Technology
External Glove Surface	Smooth with Micro-Textured Finish
Internal Glove Surface	Polymer Coated with DERMASHIELD™ Technology
Allergy Prevention	Latex (Type I)
Grip Level	Moderate
Double Gloving Recommendation	Outer glove or underglove
Tested For Use With Chemotherapy Drugs	Yes, in accordance with ASTM D6978 and US FDA cleared
Freedom from Holes (Inspection level I)	0.65 AQL
Product Standards	AS/NZS 4179, ASTM D3577, ASTM D6978, ASTM D7160, ASTM F739, EN 16523-1, EN 374:2003 Microorganism, EN 374:2003 Low Chemical Resistant, EN 420:2003 + A1:2009, EN 455 1-4, EN ISO 374-1:2016, EN ISO 374-5:2016, ISO 10282, JIS T9107
Quality / Environmental Standards	EN556, ISO 11137-Part 1, ISO 13485, ISO 14001, ISO 9001
Packaging	50 pairs per box; 4 boxes per carton/case; 200 pairs per carton/case
Shelf Life	3 years
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Vulcanization Chemical Accelerators	<ul style="list-style-type: none">• Xanthates• Zinc Dialkyldithiocarbamate