

GAMMEX® Non-Latex PI Micro

S U R G I C A L G L O V E S

Polyisoprene, skin-friendly surgical glove with exceptional dexterity and tactile sensitivity for surgical finesse

KEY FEATURES AND BENEFITS:

- 15% thinner on average than Ansell's standard polyisoprene surgical gloves for unsurpassed dexterity and tactile sensitivity
- Softer and 'stretchier' PI glove featuring superior comfort compared to Ansell's latex gloves
- Smooth with micro-textured finish for exceptional instrument handling and grip

Recommended For

- All surgeries, especially delicate procedures in ophthalmology, micro, and cardiovascular
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Protection from chemical accelerators such as thiurams, carbamates and mercaptos known to cause chemical Type IV allergies
- Having passed the Mouse Embryo Assay (MEA) test, may be used for In Vitro Fertilization (IVF) procedures

FEATURED TECHNOLOGIES



GAMMEX® Innovation that Protects

Driven by innovation, GAMMEX® surgical gloves are engineered to respond to the evolving user needs of the surgical community. Featuring unique formulations and cutting-edge technologies, ergonomic comfort and superior protection, healthcare workers around the world entrust their hands to ours.

GAMMEX® Non-Latex PI Micro

S U R G I C A L G L O V E S

PRODUCT INFORMATION

| | |
|--|--|
| Material | PI (Polyisoprene) |
| Powder Content | Powder-Free |
| Color | White |
| Thickness | Micro |
| Cuff Style | Beaded with SUREFIT™ Technology |
| External Glove Surface | Smooth with Micro-Textured Finish |
| Internal Glove Surface | Polymer Coated with DERMASHIELD™ Technology |
| Allergy Prevention | Latex (Type I) |
| Grip Level | Moderate |
| Double Gloving Recommendation | Outer glove |
| Tested For Use With Chemotherapy Drugs | No, not tested in accordance with ASTM D6978 |
| Freedom from Holes (Inspection level I) | 0.65 AQL |
| Product Standards | AS/NZS 4179, ASTM D3577, ASTM D7160, EN 16523-1, EN 374:2003 Microorganism, EN 374:2003 Low Chemical Resistant, EN 420:2003 + A1:2009, EN 455 1-4, EN ISO 374-1:2016, EN ISO 374-5:2016, JIS T9107 |
| Quality / Environmental Standards | EN556, ISO 11137-Part 1, ISO 13485, ISO 14001, ISO 9001, Korean GMP |
| Packaging | 50 pairs per box; 4 boxes per carton/case; 200 pairs per carton/case |
| Shelf Life | 3 years |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> • Xanthates • Zinc Dialkyldithiocarbamate |